Material Safety Data Sheet

SDS date: 03-10-2017 **SDS version: 1.1**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Trade Name: Lasergas 3,5-10% CO
Product- no.: -

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: Lasergas.

1.3. Details of the supplier of the safety data sheet

Company and address
Strandmøllen A/S
Strandvejen 895
DK-2930 Klampenborg
Tlf.: +45 701 02 107
www.strandmollen.dk

Contact person and E-mail:
kundeservice@strandmollen.dk

The Safety data sheet is completed and validated by:
mediator A/S, Centervej 2, DK-6000 Kolding. Consultant: HG

1.4. Emergency telephone number

Use your national or local emergency number - See section 4 “First aid measures”.

SECTION 2: Hazards identification

2.1. Classification of substance or mixture

CLP (1272/2008): Press. Gas (Compressed);H280, Repr. 1A;H360D, STOT RE 2;H373.
See full text of H-phrases in section 16.

2.2. Label elements

Signal word:
Danger

Contains gas under pressure; may explode if heated. (H280)
May damage the unborn child. (H360D)
Causes damage to organs through prolonged or repeated exposure by inhalation. (H372)

Obtain special instructions before use. (P201)
Wear protective gloves/protective clothing/eye protection/face protection. (P280)
IF exposed or concerned: Get medical advice/attention. (P308+P313)
Protect from sunlight. Store in a well-ventilated place. (P410+P403)

2.3. Other hazards

Contains carbon monooxide.

Additional labelling:

-

Additional warnings:

Careful! Inhalation of a small amount of helium can lead to suffocation.

SSECTION 3: Composition/information on ingredients

3.1./3.2. Substances/Mixtures

Substance	EU-Index no.	CAS / EINECS no.	DSD classification/CLP-classification	w/w %	Note
Helium	-	7440-59-7 / 231-168-5	Press. Gas;H280	1-100	-
Nitrogen	-	7727-37-9 / 231-783-9	Press. Gas;H280	1-100	-
Carbon dioxide	-	124-38-9/ 204-696-9	Press. Gas; H280	1-20	1
Carbon monooxide	006-001-00-2	630-08-0/ 211-128-3	Flam. Gas 1;H220, Press. Gas 1;H280, Acute Tox. 3;H331, Repr. 1A;H360D, STOT RE 1;H372	3,5-10	-

1 = The substance has a national exposure limit.

See full text of H-phrases in section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: Seek fresh air. Keep victim under observation. Seek medical advice in case of discomfort.

Ingestion: Not relevant as the product is a gas. Wash out mouth thoroughly and drink 1-2 glasses of water in small sips.

Skin contact: On frostbite: rinse with plenty of lukewarm water (max 37°C). Do not remove clothes until thawed. Seek medical advice.

Eye contact: Flush immediately with water (preferably using eye wash equipment) for at least 5 minutes. Open eye wide. Remove any contact lenses. Seek medical advice.

Additional information: When obtaining medical advice, show the safety data sheet or label.

4.2. Most important symptoms and effects, both acute and delayed

May damage the unborn child. Causes damage to organs through prolonged or repeated exposure by inhalation. Risk of suffocation at high concentrations in tight spaces.

4.3. Indication of any immediate medical attention and special treatment needed

No special immediate treatment required.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Extinguish with powder, foam or water mist. Do not use water stream, as it may spread the fire.

5.2. Special hazards arising from the substance or mixture

Avoid inhalation of vapour and fumes – seek fresh air. Heating will cause a rise in pressure in packaging with a risk of bursting. Use water or water mist to cool non-ignited stock.

5.3. Advice for firefighters

Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases – seek fresh air.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment – see section 8. Stay upwind/keep distance from source. Take precautionary measures against static discharges. Use spark-free tools and explosion proof equipment. Emergency-response personnel: protective suit equivalent to EN 368, type 3, is recommended.

6.2. Environmental precautions

Avoid unnecessary release to the environment.

6.3. Methods and material for containment and cleaning up

Not relevant as the product is a gas.

6.4. Reference to other sections

See above.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

See section 8 for information about precautions for use and personal protective equipment. Smoking and naked flames prohibited. Work under effective process ventilation (e.g. local exhaust ventilation). Running water and eye wash equipment must be available. Make sure all hoses and fittings are tight. All fittings, pipes, wires and fittings must be free of oil, grease and other oxidizable materials (for example solvents).

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container: Do not expose to temperatures exceeding 50 °C. Store in a well-ventilated area. The flasks must be stored and utilized in an upright position and must be secured with a chain.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits:

Substance	Long-term exposure limit	Short-term exposure limit	Note
Carbon dioxide	5000 ppm – 9150 mg/m^3	15000 ppm – 27400 mg/m^3	-
Carbon monooxide	30 ppm – 35 mg/m^3	200 ppm – 232 mg/m^3	BMGV

BMGV = Biological monitoring guidance values.

DNEL and PNEC values:

DNEL – Carbon monooxide:

Inhalation	Short term	Systemic effects	Workers	117 mg/m^3
Inhalation	Short term	Local effects	Workers	117 mg/m^3
Inhalation	Long Term	Systemic effects	Workers	23 mg/m^3
Inhalation	Long Term	Local effects	Workers	23 mg/m^3

8.2. Exposure controls

There are no exposure scenarios for this product.

Appropriate engineering controls:

Wash hands before breaks, before using restroom facilities, and at the end of the work. Wear personal protective equipment specified in below section.

Personal protective equipment:

Breathing equipment:	In case of insufficient ventilation, wear respiratory protective equipment. Use air-supplying respiratory protective equipment (EN 136/140/145).
Hand protection:	Recommended: Leather gloves.
Eye protection:	Wear safety goggles if there is a risk of eye splash (EN 166).
Body and skin protection:	Use safety shoes when handling flask.

Environmental exposure controls:

Ensure compliance with local regulations for emissions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form:	Gas
Colour:	Colourless
Odor:	Odourless - weak
pH:	-
Melting point/ Freezing Point (°C):	-
Initial boiling point(°C):	-
Decomposition temperature (°C):	-
Flash point (°C):	-
Evaporation speed:	-
Ignition (°C):	-
Upper / lower Flammability or Explosion limits (vol-%):	-
Vapour pressure (bar, 20 °C):	-
Vapour density (air=1)	-
Density:	Lighter than air
Solubility in water (mg/l):	-
Partition coefficient [n-octanol/water], Log K_{OW}:	-
Critical temperature (°C):	-
Evaporation rate (nBuAc=1):	-
Viscosity:	-
Flammability:	-
Oxidizing properties:	-

9.2. Other information

Molecular weight:	-
Surface tension (mN/m, 25 °C):	-

SECTION 10: Stability and reactivity

10.1. Reactivity
Non-reactive
10.2. Chemical stability
The product is stable when used in accordance with the supplier's directions.
10.3. Possibility of hazardous reactions
No risk of hazardous reactions.
10.4. Conditions to avoid
Avoid heating and contact with ignition sources.
10.5. Incompatible materials
None known.
10.6. Hazardous decomposition products
Nitrogen forms nitrides with active metals, such as. calcium, lithium, magnesium and titanium at high temperatures.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Substance	Route of exposure	Species	Test	Result
Carbon monooxide	Inhalation	Rat	LC50 / 4 h	ca. 1300 ppm

Symptoms:

Inhalation: Inhalation of a small amount of helium can lead to suffocation. In severe cases, the gas can replace the atmospheric air, so there can be a choking hazard. Symptoms may include rapid pulse, deep breathing and slight dizziness and at higher concentrations loss of mobility and loss of consciousness. The exposed person may not notice suffocation.

Skin contact: Not relevant as the product is a gas.

Eye contact: Not relevant as the product is a gas.

Ingestion: During normal handling gases can not be consumed.

Long term effects:

May damage the unborn child.

Causes damage to organs through prolonged or repeated exposure by inhalation.

SECTION 12: Ecological information

12.1. Toxicity

Substance	Test duration	Species	Test	Result
No data	-	-	-	-

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
No data	-	-	-

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
No data	-	-	-

12.4. Mobility in soil

-

12.5. Results of PBT and vPvB assessment

No data.

12.6. Other adverse effects

None.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The product should be treated as dangerous waste.

EWC Code

16 05 04

Rented flasks should be disposed of via supplier.

Specific labelling

-

Contaminated packaging:

Uncleansed packaging is to be disposed of via the local waste-removal scheme.

SECTION 14: Transport information

This product is included in the regulation of dangerous goods.

14.1 -14.4.

ADR

UN number.:	UN proper shipping name	Transport hazard class(es)	Packing group
1956	COMPRESSED GAS, N.O.S. (Helium, nitrogen, carbon dioxide)	2.2 	-

IMDG

UN-no.:	Proper shipping name	Transport hazard class(es)	Packing group
1956	COMPRESSED GAS, N.O.S. (Helium, nitrogen, carbon dioxide)	2.2 	-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

-

Restrictions for application:

-

Demands for specific education:

-

15.2. Chemical safety assessment

Chemical safety assessment has not been performed.

SECTION 16: Other information

Other information:
Sources:
EC regulation 1907/2006 (REACH)
Directive 2000/532/EC
EC Regulation 1272/2008 (CLP)
EH40/2005 WELs (United Kingdom (UK), 8/2007).
Full text of H-phrases as mentioned in section 2+3:
H220 - Extremely flammable gas.
H280 - Contains gas under pressure; may explode if heated.
H331 - Toxic if inhaled.
H360D - May damage the unborn child.
H372 - Causes damage to organs through prolonged or repeated exposure by inhalation.
Other
-
Minor changes have been made in following sections:
1 – 16.
This material safety data sheet replaces version:
1.0 (17-03-2015)